# Interfor Elite V-Joint Paneling



Interfor Elite Cedar V-Joint Paneling offers the ultimate in quality appearance, combining the exceptional beauty and outstanding performance of Western Red Cedar with our consistent manufacturing excellence. As one of the world's largest suppliers of Western Red Cedar, Interfor has a reliable fiber supply to provide the perfect product when it is needed.

Interfor.com







**Western Red Cedar** 



**V-Joint Paneling** 



**Paneling** 



**BC Interior** 



# INTERFOR ELITE V-JOINT PANELING

#### **BEST CHOICE FOR APPEARANCE**

Western Red Cedar offers beauty, rich color and exceptional building properties, and it is manufactured to exacting standards through our kiln and planer facilities. Properly finished and maintained, Western Red Cedar ages gracefully and lasts for years.

Interfor Elite V-Joint Paneling features straight, even grain; uniform texture; and sound, tight knots that will not fall out over time. It is reversible — smooth on one face and saw-textured on the other — and can be installed with either side exposed. The sawn face adds an appealing texture to the finished project. The product is available in both a V4E and V2E pattern.

#### **BEST FOR QUALITY & PERFORMANCE**

One of the easiest woods to work, Western Red Cedar is dimensionally stable, lightweight, strong and versatile, and is naturally resistant to decay and insect damage. Interfor Elite V-Joint Paneling is easy to saw and glue, and accepts nails and other fasteners.

IMPERIAL SIZE nominal inches	IMPERIAL SIZE actual inches	DRESSING	SEASONING	PIECES PER BUNDLE	PIECES PER PACKAGE	LENGTH (feet)
1 x 4	11/16 x 3 <sup>3/8</sup>	Smooth Face/ Resawn Back	Kiln-Dried	6	2,200 fbm	6-20 O&E 6-20 PTL
1 x 6	11/16 x 5 <sup>3/8</sup>	Smooth Face/ Resawn Back	Kiln-Dried	6	2,200 fbm	6-20 O&E 6-20 PTL
1 x 8	11/16 x 7 <sup>3/8</sup>	Smooth Face/ Resawn Back	Kiln-Dried	6	2,200 fbm	6-20 O&E 6-20 PTL

### **FINISHING AND MAINTENANCE**


- Western Red Cedar is pitch and resin-free, making it an excellent base for paints and stains.
- · Western Red Cedar should never weather for more than two weeks before finishing. All finishes adhere and perform better when applied to fresh, unweathered wood.
- Power washers are not recommended for use on Western Red Cedar.
- For best results, Western Red Cedar should be coated

The cellular structure and insulation value of Western Red Cedar means that buildings featuring Cedar paneling, ceilings or siding are cooler in the summer and warmer in the winter. The wood also suppresses and absorbs sound.


Tongue and groove is widely used for its appearance and versatility. Interfor Elite V-Joint Paneling can be installed vertically, horizontally or diagonally, with each method giving a distinctly different look.

#### **BEST FOR ENVIRONMENT**

Wood from responsible sources is by far the best building choice. Wood grows naturally, it is recyclable and renewable, and its cellular structure captures and stores carbon. Interfor meets the highest environmental standards, and our quality Western Red Cedar comes from forests in British Columbia that are third-party certified. Western Red Cedar's natural oils that act as preservatives protect against decay and insects so harmful chemical treatment is not needed.



- on all sides before installation. Factory finishing, where available, is preferred.
- Corrosion-resistant nails such as hot-dipped galvanized aluminum and stainless steel are recommended.
- More detailed information about finishing and maintenance is available from the Western Red Cedar Lumber Association website at www.realcedar.com/ resources/brochures-literature/.





Interfor is a growth-oriented lumber company with operations in Canada and the United States. The Company has annual production capacity of 3.1 billion board feet and offers one of the most diverse lines of lumber products to customers around the world.

## Interfor.com

North America, Cedar PHONE (604) 422-3400 FAX (604) 422-3244 EMAIL cedarsales@interfor.com 1600-4720 Kingsway Burnaby, BC Canada V5H 4N2

**INTERFOR** 

